



Satellite Dishes & Cable Products -> Metal Line -> Satellite antenna PF85



SATELLITE DISHES & CABLES

PF85



Satellite antenna



Technical

TECHNICAL DATA

Dish dimensions (external) (mm)	880x880
Gain at 10,75 GHz (dB)	38,1
Gain at 11,75 GHz (dB)	38,7
Gain at 12,75 GHz (dB)	39,5
Half power beamwidth at 12,75 GHz (deg)	< 2,1°
Cross polar discrimination on main axis (dB)	> 27
Mast clamp for (mm)	32 - 76
Elevation range (deg)	7° - 53°
Elevation with passing pole (deg)	44°
F/D ratio	0,6
Offset angle (deg)	21,5°
Windloading at 72 Km/h (Kg)	21
Windloading at 144 Km/h (Kg)	85
Windloading at 216 Km/h (Kg)	192
Feed bracket diameter (mm)	23 / 40

Available reflector materials	steel/aluminium
Available colours	white/anthracite/red
Back mount made of	galvanized steel + plastic insert
AZ/EL holder made of	galvanized steel
LNB Arm (48x22mm) made of	aluminium
LNB holder made of	plastic

2022 © © TELE System Digital Srl - Italy

Website owner: TELE System Digital S.r.l. - Registered office: Via dell'Artigianato, 35, 36050 Bressanvido (VI) - Italy

Tax Code 90007180269 - VAT IT03775980240 - R.E.A. VI-357837

[Privacy Policy](#)