


Draka UC400 Cat. 6 U/UTP 23 AWG PVC & LSZH

Ethernet cable up to 250 MHz



Application

Generic cabling systems
 Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
 IEEE 802.3 10Base-T; 100Base-T; 1000Base-T
 IEEE 802.5 16 MB; ISDN; TPDDI; ATM
 IEEE 802.3af (PoE); IEEE 802.3at (PoE+)

Standards

ANSI EIA/TIA 568-D.2: 2018;
 ISO/IEC 11801-1: 2017 / ISO/IEC 11801-2: 2017;
 IEC 61156-5: 2012;
 EN 50173-1: 2011 / EN 50173-2: 2007 including amendment A1: 2010
 EN 50288-6-1: 2013

Construction

Conductor	Solid copper wire Nom. $\geq \varnothing 0.546$ mm (23AWG)
Insulation	PE, Nom. $\varnothing 0.95/1.01$ mm
Twisting	2 cores to the pair
Cable Lay Up	4 x pairs to the core non-metallic cross separator
Sheath / Color	PVC & LSZH: GREY (RAL7035); BLUE (RAL5012)
Outer Diameter	Nom. $\varnothing 6.1$ mm
Approximate Weight	Nom. 39.0 kg/km

Mechanical properties

Bend radius	With Load	≥ 8 x O.D
	No Load	≥ 4 x O.D
Temperature range	During operation	-20°C to +60°C
	During installation	0°C to +50°C
Maximum Pulling Force	During installation	100 N

Electrical properties

Mean Characteristic Impedance	1-100 MHz	100 ± 15 Ω
	100-250 MHz	100 ± 22 Ω
DC Loop Resistance		Nom. 150 Ω/km
DC Resistance Unbalance		≤ 5%
Mutual Capacitance (@1 kHz)		≤ 5.6 nF/100m
Capacitance unbalance	Pair to ground	≤ 330 pF/100m
Velocity of Propagation		Nom. 65%
Propagation Delay (@250 MHz)		≤ 536.0 ns/100m
Delay Skew		≤ 45 ns/100m

Freq. (MHz)	Max. Attenuation (dB)	Min. NEXT (dB)	Min. PS-NEXT (dB)	Min. ACR-F (dB)	Min. PS-ACRF (dB)	Min. Return Loss (dB)
1.0	2.0	74.3	72.3	67.8	64.8	20.0
4.0	3.8	65.3	63.3	55.8	52.8	23.0
16.0	7.6	56.2	54.2	43.7	40.7	25.0
25.0	9.5	53.3	51.3	39.8	36.8	24.3
62.5	15.4	47.7	45.7	31.9	28.9	21.5
100.0	19.8	44.3	42.3	27.8	24.8	20.1
200.0	29.0	39.8	37.8	21.8	18.8	18.0
250.0	32.8	38.3	36.3	19.8	16.8	17.3

Note1: All tests include 401 points swept frequency measurements

Note2: All electrical characteristics are given at 20°C

note3: All above stated values are nominal and subject to changes

Note4: Transmission performance based on 100 m (328 ft)

Fire Rating

PVC IEC 60332-1-1: 2015; IEC 60332-1-2: 2015;

LSZH IEC 60332-1-1: 2015; IEC 60332-1-2: 2015;

IEC 60754-1: 2011; IEC 60754-2: 2011;

IEC 61034-2: 2013

Ordering Information

SAP 1C	UC P/N	Product Description	P.U
60067185	60075	UC400 Cat 6 UUTP 23 AWG LSZH GREY	305 m/box
60067295	60075	UC400 Cat 6 UUTP 23 AWG LSZH GREY	500 m/reel
60078576	60075OR	UC400 Cat 6 UUTP 23 AWG LSZH ORANGE	305 m/box
60078837	60075GN	UC400 Cat 6 UUTP 23 AWG LSZH GREEN	305 m/box
60067294	60088	UC400 Cat 6 UUTP 23 AWG PVC GREY	305 m/box
60067734	60088BL	UC400 Cat 6 UUTP 23 AWG PVC BLUE	305 m/box

Marking:

Marked in 1 meter intervals as follows:

DRAKA UC400 U/UTP <SHEATH> CAT 6 CABLE P/N <PART NUMBER> VERIFIED TO EN 50288 ISO/IEC 11801 ANSI/TIA-568-C.2 <FC> <BATCHCODE> <XXX>M

<SHEATH>: PVC / LSZH

<PART NUMBER>: Cable part number

<FC>: Draka defined factory Code

<BATCHCODE>: Factory defined tracking code MM/YYYY or WW/YYYY

<XXX>: Increasing length marking by 1 metre

Logistic

Packing:

Reellex II box or Wooden drum.

Delivery Lengths:

305m per box or 500m per drum.

Enquiries

Please contact our local sales office or mms.asia@prysmiangroup.com

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UC CONNECT for a complete Structure Cabling Solutions with 25 Years System Warranty.

Visit www.DrakaUC.com for more information.

© PRYSMIAN GROUP 2019, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.