

6-way splitters

Type	Insertion loss, typical IN-OUT (dB ± 0.5) Frequency range (MHz)				Isolation, typical / minimum OUT-OUT (dB) Frequency range (MHz)				Item no.
	10-470	470-862	862-1006	1006-1300	10-470	470-862	862-1006	1006-1300	
SIS 06	8.4	9.0	9.4	9.9	33 / 23	28 / 20	28 / 20	28 / 18	48006

Return loss: Grade 1
Connectors: F-Female
Dimensions: 196 x 50 x 16 mm
Weight: 207 g



8-way splitters

Type	Insertion loss, typical IN-OUT (dB ± 0.5) Frequency range (MHz)				Isolation, typical / minimum OUT-OUT (dB) Frequency range (MHz)				Item no.
	10-470	470-862	862-1006	1006-1300	10-470	470-862	862-1006	1006-1300	
SIS 08	10.1	10.7	11.2	11.9	33 / 24	32 / 22	31 / 20	30 / 20	48008

Return loss: Grade 1
Connectors: F-Female
Dimensions: 196 x 50 x 16 mm
Weight: 214 g



accessories for signia taps and splitters

Signia taps and splitters can be fitted with a set of spacers to allow easy installation of cables beneath the units. With a height of 8 mm it allows space for the most commonly used installation cables.

The spacers are easily snapped on if extra space is required.



Type name Signia FS, item no. 49120

